

## Complete Multiple Tasks in One with Easy-to-read Color Touch Screen.

Pantum M7300 series makes your jobs easier with 3.5 inch color touch screen. It makes your work more efficient with multifunction in one, high print and copy speed and auto-duplex printing and scanning meanwhile makes your outputs more affordable and eco-friendly with separate drum unit and toner cartridge. It aims to meet the requirements of small to large workgroups using satisfying function and outstanding performance.



**MONO**

**Easy-to-read** 3.5 inch color touch screen



**Automatic Duplex  
Printing and Scanning**



**Confidential  
Printing**



**Wifi One Step Installation  
and Direct Printing**



**USB Disk Direct  
Printing**

# KEY SPECIFICATIONS

Model	M7300FDN	:	M7300FDW
<b>Printing</b>			
Print speed <sup>(1)</sup>	33ppm (A4) / 35ppm (Letter)		
Time to First Page <sup>(1)</sup>	≤8.5s		
Maximum Monthly Duty Cycle	60000 Pages		
Recommended Monthly Page Volume	750 to 3500 Pages		
Print Resolution	Max 1200x1200 dpi		
Printer Languages	PCL5e, PCL6, PS, PDF		
Processor	600MHz		
Memory	512 MB		
Duplex Printing	Auto		
Control Panel	3.5 inch touch screen		
USB Printing	Yes		
Security Printing	Yes		
Google Cloud Printing	Yes		
NFC Connection	No	:	Yes
<b>Copying</b>			
Copy Speed <sup>(1)</sup>	33cpm (A4) / 35cpm (Letter)		
Time to First Copy <sup>(1)</sup>	Flatbed: Less than 10s / ADF: Less than 11s		
Copy Resolution	Max 600 x 600dpi		
Continuous Copy Page	1-99 Page(s)		
Zoom	25%~400%		
Additional Function	ID copy, Receipt copy, N-up copy, Clone copy, Poster copy, Manual duplex copy, Collated copy		
<b>Scanning</b>			
Scan Type	Flatbed+ADF		
Duplex Scanning <sup>(1)</sup>	Yes, 24ppm (48ipm)		
ADF Capacity	50 Pages		
Scan Speed <sup>(1)</sup>	24 ppm (A4) / 25 ppm (Letter)		
Max Scan Size	Flatbed: 216 x 297mm ADF: 216 x 356 mm		
Scan Resolution	Flatbed: Max 1200 x 1200dpi ADF: Max 600 x 600dpi		
Color Scanning	Yes		
Output Function	Scan to PC, Email, FTP, USB		
<b>Faxing</b>			
Fax Type	Mono		
Modem Max Speed	33.6Kbps		
Fax Resolution	Max 300 x 300 dpi		
Fax Memory	650 Pages		
Coded System	MH / MR / MMR / JBIG		
Compatibility <sup>(1)</sup>	ITU-T SG3 / ECM		
Fax Feature	PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, Delayed Send, Auto Redial, Auto Receive, Auto Reduction, Fax To Email ; PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, Delayed Send, Auto Redial, Auto Receive, Auto Reduction, Mobile Fax, Fax To Email		
<b>Paper handling</b>			
Paper Input Tray	250 Pages		
Multipurpose Tray	1 Page		
Paper Output Capacity	150 pages (A4/70g)		
Media Type	Plain, Thick, Thin, Transparency, Cardstock, Label, Envelope		
Media Size	A4, A5, JIS B5, ISO B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2		
Media Weight	Standard Tray: 60-105g/m <sup>2</sup> Multipurpose Tray: 60-200g/m <sup>2</sup>		
<b>General</b>			
Product Dimension (wxdxh)	415 x 360 x 352mm		
Weight (without toner cartridge)	10.54kg		
Environment	Best Temperature: 10~32°C Relative Humidity: 20%~80%		
Noise	Print: 52dB(A) Copy: 54dB(A) Scan: 52dB(A) Standby: 30dB(A)		
Power Consumption	Print: Average 550W Standby: Less than 50W Dormant: Less than 2W		
Operating System	Microsoft Windows Server 2003/Server 2008/Server 2012/XP/Vista/Win7/Win8/Win8.1/Win10(32/64 Bit); Mac OS 10.7-10.12; Linux: Ubuntu 12.04/14.04(32/64 Bit)		
Mobile Operating system compatibility	: iOS 7.0 and above; Android 4.4 and above		
Interface	High Speed USB 2.0 : Net: IEEE 802.3 10/100Base-Tx ; High Speed USB 2.0 : Net: IEEE 802.3 10/100Base-Tx WiFi: IEEE 802.11b/g/n		
<b>Supplies</b>			
Cartridge Type	Separate Drum and Toner		
Starter Cartridge / Drum Unit <sup>(2)</sup>	1500 Pages / 12000 Pages		
Replacement Cartridge <sup>(2)</sup>	TL-410 (1500 pages), TL-410H (3000 pages), TL-410X (6000 pages)		
Replacement Drum Unit <sup>(2)</sup>	DL-410 (12000 pages)		

<sup>(1)</sup> Up to

<sup>(2)</sup> As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)

Copyright © 2017 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.