

# PANTUM

The New Era for Printing

**P3010 Series**  
Monochrome Laser Printer

## Offer eco-friendly and affordable prints whenever you need it

Start a worry-less printing with the new Pantum P3010 series today that has extremely low paper jam rate and highly budget-saving and more eco-friendly separate drum unit and toner cartridge. It is designed for users from SMB to large workgroup requiring easy-to-use and cost-effective office tools for their rapidly growing business.



Silent printing mode to lower the noise  
and create a comfortable office environment



**High**  
Print Speed



**LOW** paper jam rate  
design for engine



**Convenient**  
to Print



**Separate**  
Drum and Toner

**PANTUM**

[WWW.PANTUM.COM](http://WWW.PANTUM.COM)

# KEY SPECIFICATIONS



## P3010 Series Monochrome Laser Printer

Model P3010D | P3010DW

### Printing

Print technology	Mono laser	
Print speed	30ppm(A4)/32ppm(Letter)	
First print out time	7.8 seconds	
Max. monthly volume	60,000 pages	
Recommended monthly volume	750 to 3,500 pages	
Processor speed	350 MHz	
Memory	128 MB	
Resolution(dpi)	Up to 1,200 x 1,200 dpi	
Printer language	GDI	
Duplex mode	Auto	
Control panel	LED	2Line LCD
NFC print	No	Yes
Network print	No	Yes
Wireless print	No	Yes

### Paper handling

Paper input tray	250 sheets	
Multipurpose tray	1 sheet	
Paper output tray	150 sheets	
Media types	Plain,Thick,Transparency,Cardstock,Lable,Envelope	
Media sizes	A4, A5, JIS B5, Is0 B5 , A6, Letter, Legal,Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2 , Custom	
Media weight	Input tray: 60-105g/m <sup>2</sup> Multipurpose tray: 60-200g/m <sup>2</sup>	

### General

Dimensions (wxdxh)	354 x334x 218mm(13.9x 13.1x8.6in)	354 x334x 232mm(13.9x 13.1x9.1in)
Weight (without toner cartridge )	6.8kg (15lb)	
Operating temperature range	10-32°C (50-95°F)	
Operating humidity range	20% - 80% RH	
Input voltage	110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%,+10%), 50/60Hz(±2Hz), 4.5A	
Noise	Printing: ≤52dB(A) Standby: ≤30dB(A)	
Power consumption	Print: Average 525W Standby: 50W Dormant: Less than 2W	
Operating system compatibility	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.12; Linux (ubuntu12.04/14.04);	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.12; Linux (ubuntu12.04/14.04); iOS 7.0 and above Android 4.4 and above
Interface	High-speedUSB2.0	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx Wifi: IEEE 802.11b/g/n

### Supplies

Cartridge style	Separate drum and toner	
Starter cartridge capacity <sup>(1)</sup>	TL-410E (1,000 pages)	
Cartridge and drum capacity <sup>(1)</sup>	Cartridge: TL-410 (1,500 pages, Standard); TL-410H (3,000 pages, High); TL- 410X (6,000 pages, Extra high) Drum: DL-410 (12,000 pages)	
Starter drum unit lifetime <sup>(1)</sup> <small>(Print with A4 paper page by page discontinuously)</small>	DL-410E (9,000 pages)	

### What s in the box

Printer × 1/1,000 pages Toner Cartridge × 1/9,000 pages Drum unit × 1/ USB Interface Cable × 1/  
Power Cord × 1/ CD-ROM × 1/ Quick Setup Guide × 1

<sup>(1)</sup> Average yield per toner cartridge in accordance with ISO/IEC 19752 (Individual users will experience different results based on their environment and page coverage)

Copyright ©2017 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.